



FEATURES:

- ACCOMMODATE UNIVERSAL AC INPUT
- GREEN POWER
- MEET UNIVERSAL SAFETY STANDARDS
- EMI MEET FCC, CISPR 22 CLASS B
- CE MARKING COMPLIANCE

SPECIFICATION

INPUT SPECIFICATION

Input Voltage: 90-264Vac typical.
Input Connector: USA/Euro/Aust.
Input Frequency: 47-63Hz.
Inrush Current: 20A@115Vac cold start 25 °C.
Input Current: max 400mA@115Vac.
EMI: FCC part 15 Class B, CISPR 22 Class B
Hold-up Time: >10mS @ full load; 115Vac typical
Standby power dissipation: <0.3W

OUTPUT SPECIFICATION

Output Voltage: +3.3V ~ +24Vdc
Output Current: 0.10A – 2.5A
Output Wattage: 12.5 Watts typical.
Output Connector & Cord: Optional.
Line Regulation: ± 1.0% typical.
Load Regulation: ± 5.0% typical.
Noise & Ripple: 1% peak to peak typical.
OVP: Build-in.
Overload Protection (OLP): Fully protected against short circuit and over current. Consult the factory for OLP setting.

GENERAL SPECIFICATION

Efficiency: >75% @ full load.
Safety Standard: UL/cUL, CB, TUV GS, C-Tick

Operating Temperature: 0 to +40°C.
Storage Temperature: -10 to +60 °C.
Cooling: Free air convection
Construction: Impact resistant plastic case;
wall-mount format.

Note:
1. All measurements are at nominal input, full load, and +25 °C unless otherwise specified.
2. The exact obtainable load regulation depends upon the output cord selected and load current.
3. Due to requests in market and advances in technology, specifications subject to change without notification.



OUTPUT VOLTAGE / CURRENT RATINGS CHART

SINGLE OUTPUT *(Model No. for example)*

MODEL NO.	VOLTAGE	CURRENT (MAX)
PA1015-XXXXXX	3.3~24.0V	0.10~2.50A

MECHANICAL DIMENSIONS: 67x27.5x50MM

WEIGHT: 130g

