

Interchange AC Plug Wall Mount Type Switching Power Adaptor

- ◆ Interchange AC Plug **No Screw** Design
- ◆ The best idea to **reduce stock**, the most cost efficiency adaptor for exporter
- ◆ Output Watt for **5W to 30W** (4 models)
- ◆ Light Weight and Compact Size
- ◆ Over-Voltage Protection Installation
- ◆ Short Circuit Protective Installation
- ◆ Protection Type: Auto Recovery
- ◆ Operating Temperature: 0~40°C
- ◆ **CEC** Efficiency Regulations (Optional)



No Screw Design Easy To Change
AC Plug; Just (1)Push & (2)Rotate



SPECIFICATION

Item	Model	PA-1005-IB	PA-1010-IB	PA-1020-IB	PA-1030-IB
Output Power		5W	10W(12W)	20W	30W
Output Voltage		3.3 / 5 / 6 / 7.5 / 9 / 12 / 15 / 24 / 30VDC (9 versions)			
Input Voltage / Frequency		AC 90~264V / 47~63 Hz			
Inrush Current		40A Maximum			
Line Regulation		2% Maximum			
Load Regulation		+/- 5%			
Ripple & Noise		1% Typical			
Efficiency		Over 60% Typical			
Temperature Coefficient		0.05% / °C			
Over-Voltage Protection		Auto Recovery			
Short-circuit Protection		SAuto Recovery (<0.03 ohm)			
Operating Temperature		0~40°C			
Storage Temperature		-20~85°C			
Safety		TUV EN60950, CB, UL60950, CE, PSE, BSMI			
EMC (EMI/EMS)		Cisrp 22 Class B, EN 55022 Class B, FCC, BSMI			



Manca Limited
美佳達有限公司
<http://www.manca.hk>

香港荃灣沙咀道11號 | Flat 1301, 13/F., International Trade Centre,
達貿中心13樓1301室 | 11 Sha Tsui Road, Tsuen Wan, Hong Kong.

Tel: +852 3595 0235
Fax: +852 3020 2234